

NOV 16 2001

US005984190A

United States Patent
Nevill

MAIL DATE CANCELLED
NOV 19 2001

Patent Number: 5,984,190
Date of Patent: Nov. 16, 1999

[54] METHOD AND APPARATUS FOR
IDENTIFYING INTEGRATED CIRCUITS

578 410 A2 1/1994 European Pat. Off. G06F 11/00
3138085 A1 4/1983 Germany H01L 21/66
3226733 A1 7/1983 Germany H01L 23/50
2244339 11/1991 United Kingdom G01R 31/28

[75] Inventor: Leland R. Nevill, Boise, Id.

[73] Assignee: Micron Technology, Inc., Boise, Id.

Primary Examiner—Donald Hajec
Assistant Examiner—Daniel St. Cyr
Attorney, Agent, or Firm—Seed and Berry LLP

[21] Appl. No.: 08/857,100

[22] Filed: May 15, 1997

[51] Int. Cl.⁶ G06K 19/06

[52] U.S. Cl. 235/492; 235/494; 438/10;
438/18

[58] Field of Search 235/492, 493,
235/494, 487; 438/10, 18

[56] References Cited

U.S. PATENT DOCUMENTS

4,967,381	10/1990	Lane et al.	364/551.01
5,103,166	4/1992	Jeon et al.	324/158 R
5,226,118	7/1993	Baker et al.	395/161
5,294,812	3/1994	Hashimoto et al.	257/65
5,301,143	4/1994	Ohri et al.	365/96
5,313,174	5/1994	Dubois et al.	235/454
5,380,998	1/1995	Bossen et al.	235/494
5,389,770	2/1995	Ackley	235/462
5,420,796	5/1995	Weling et al.	364/468
5,434,870	7/1995	Benton et al.	371/37.1
5,467,304	11/1995	Uchida et al.	365/174
5,511,005	4/1996	Abbe et al.	364/552
5,787,174	7/1998	Tuttle	380/23

FOREIGN PATENT DOCUMENTS

0 488 053 A1 6/1992 European Pat. Off. H01L 23/544

[57] ABSTRACT

An integrated circuit and method for identifying same is described. The integrated circuit includes a programmable identification circuit for storing electronic identification information. The integrated circuit also includes an optical identification mark displaying a machine-readable optical identification code which corresponds with the electronic identification information stored in the identification circuit. The data encoded in the optical identification code may be identical with that of the electronic identification information. Alternatively, a look-up table or other correlating means may be employed to associate the optical identification code with the electronic identification information. The integrated circuit is packaged in a housing, and another optical identification mark is placed on an external surface of the housing. This second optical identification mark displays a machine-readable optical identification code which is identical or correlated to the electronic identification information stored in the identification circuit and/or the optical identification code displayed by the optical identification mark on the integrated circuit. Consequently, convenient and traceable identification of individual integrated circuits is provided during and after manufacture.

22 Claims, 1 Drawing Sheet

